
SKYJACKER UJI 5036



DIMENSIONAL SPECIFICATIONS

36' 2" (11.02m) Horizontal side reach end mount Height to bottom of basket 45' 2" (13.75m) Working height 50' 2" (15.29m) Stowed height 12 ft 1 in (3.68m) Upper boom articulation in degrees -10° to 85° Lower boom articulation in degrees 0° to 90° Standard basket capacity 300 lbs (136kg) Maximum basket capacity 600 lbs (272kg)

MECHANICAL SPECIFICATIONS

540° Boom rotation with mechanical stop

Rotation drive is hourglass worm gear acting on a shear ball bearing Side mount basket with hyd. leveling includes upper and lower controls

All hoses are enclosed within the booms

Boom elevation by hydraulic cylinders

Lower boom is high strength steel

Upper boom is filament wound epoxy resin fiberglass and steel

Lower boom consists of a parallelogram linkage

Pedestal is welded structure with reservoir

Standard color is UTEM white powder coat

Body harness (Qty 2) with adjustable length shock absorbing lanyard incl.


Outriggers with boom interlock

RECOMMENED CHASSIS REQUIREMENTS

Vehicle GVWR 19,500 lbs
Front axle GVWR 7,500 lbs
Rear axle GVWR 14,706 lbs

UJI 5036 meets or exceed ANSI A92.2 and OSHA requirements *

* Based on 40" (1.01m) chassis frame height



CONTROLS

Full pressure individual lever locking upper controls
Turret mounted full pressure lower controls
Engine stop/start provided with "HM" hydraulics
Emergency stop is provided at basket controls
Upper control override is included
Master switch in chassis cab is provided

HYDRAULIC SPECIFICATIONS

Operating pressure 2,500 PSI
Flow rate 6 GPM
Reservoir capacity w/ sight gauge 15 Gallons (571)
Suction strainer mounted in reservoir 100 Mesh
Return line filter with bypass 10 Micro

OPTIONAL EQUIPMENT

Full pressure single stick upper controls
Continuous rotation
Fiberglass baskets with steps and doors
End mount basket
Hydraulic tool outlet at basket
12VDC or 24VDC emergency powered lowering
Hydraulic basket rotator

1-888-765-3322



Utility Truck Equipment Mfg. L.L.C. 901 Enterprise Blvd Hewitt, Texas 76643

Phone: 254-857-8204 Fax: 254-857-9253

www.UTEMbuckets.com

THIS DOCUMENT

